

ARBO

ARBOSTRIP F42

Arbostrip F42 is a medium density foam compression sealant coated one side with a strong acrylic pressure-sensitive adhesive.

MAIN APPLICATIONS

Recommended for use as a weather seal, dust seal, or in glazing of internal doors and screens. It is also suitable for make and break joints and the weather proofing and draught sealing of opening lights, ventilators and doors. It is not recommended for use in expansion joints.

APPLICATION INSTRUCTIONS

Joint Preparation

All surfaces must be clean, dry and grease free. Arbostrip F42 is supplied in roll form with a paper interleaf on the non-adhesive face. This allows the tape to be applied directly without stretching.

ACCESSORIES

Primers

Arbo Primer 2650 (500ml tin)
Yield approximately 125 metres per tin
Arbo Primer 2402 (500ml tin)
Yield approximately 200 metres per tin
Arbo Primer 2172 (500ml tin)
Yield approximately 200 metres per tin

Cleaners

Arbo Cleaner No.17- 1 Litre Tin
(Xylene based – not suitable for use with plastics or delicate finishes)
Arbo Cleaner No. 16 - 1 Litre Tin
(Alcohol Based)

Ancillary Equipment

Polyethylene Nozzles
Arbo Caulking Guns

TECHNICAL DATA	
Colours	Black,
Application Temperature:	+ 5° C to + 45° C
Service Temperature:	- 30° C to + 70° C
Chemical Resistance:	Excellent resistance to weather, oxidation, salt water, dilute alkalis and acids. Poor resistance to some solvents.
UV Resistance:	Excellent
Hardness:	40 shore 00 Butt joints (movement in tension and compression): 50 %. 100 %.
Force required to compress:	3.5N/cm ²
Compression required for weather seal	30%
Compression deflection:	2.0N/cm ²
Water Absorbtion:	5% maximum
Available sizes:	12 x 3mm, 9 x 3mm, 6 x 3mm, 12 x 6mm.

STORAGE LIFE

12 months. The conditions under which the tape is stored can affect it's performance. Storage should be in a dry, well ventilated area protected from exposure to direct sunlight.

PACKAGING

Arbostrip F42 is supplied in single rolls with a paper interleaf.

20m roll, 12 x 3mm – 15 rolls per box
20m roll, 9 x 3mm – 20rolls per box
20m roll, 6 x 3mm – 30 rolls per box

N.B. Tolerances – Thickness $\pm 10\%$, Width $\pm 1\text{mm}$

IMPORTANT: The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy of which is available on request.



CARLISLE® Adsheed Ratcliffe & Co. Ltd United Kingdom

Derby Road | Belper
Derbyshire

DE56 1WJ
United Kingdom

T +44 (0)1773 826661
F +44 (0)1773 821215

E info.arbo@ccm-europe.com
www.arbo.co.uk